

The logo consists of the word "POLIFILM" in white, uppercase, sans-serif font, centered within a dark grey circular shape that has a white, peeling-edge effect at the bottom.

PAINTED METAL EFFECTIVE PROTECTION

ALONG THE ENTIRE PRODUCTION PROCESS

A circular badge with a blue background and white text. The word "NEW" is in a large, bold, sans-serif font, and "1698CLVHS" is in a smaller, sans-serif font below it.

POLIFILM PROTECTION

FOR MATTE & ROUGH SURFACE FINISHES

As the painted metals industry continues to evolve, POLIFILM AMERICA has you covered. We have all seen the market continue to demand low gloss rough textured surfaces on their painted metal. These new textured surfaces have been a challenge for the protective film industry.

However, POLIFILM's research and development team has once again offered a solution to protecting these very hard to adhere to surfaces.



HIGH RESISTANCE

The NEW 1698CLVHS product offers all of the high strength film characteristics that you have been accustomed to from our HS family of products. Not only will this film withstand your roll forming processes it will adhere to those textured surfaces. Additionally, the film can withstand up to two months UV stability.

RELIABLE ADHESION

1698CLVHS is particularly formable and has a low restoring force. Its adhesive formulation and adhesive strength are optimally adapted to the low gloss textured surfaces. Therefore, it does not lift off and guarantees a stable adhesion.

EXCELLENCE IN FILMS

POLIFILM PROTECTION UNCOMPROMISED PROTECTION



NEW! PROTECTION SOLUTION FOR MATTE, ROUGH FINISHES

CHARACTERISTICS OF THE FILM

PRODUCT TYPE	ADHESIVE TYPE	ADHESIVE STRENGTH	FILM THICKNESS	COLOUR	UV RESISTANCE
1698CLVHS	Acrylic, water-based	High	1.6 mils	Clear	1-2 Month

- ✓ **Surface application:** The waterborne acrylic adhesive system was developed for textured and low gloss matte surface finishes. The protective masking will bond to the surface structure and ensure proper anchorage, resulting in desired adhesion, throughout the entire production / removal processes.
- ✓ **Compatibility:** The engineered adhesive formulation was designed to be compatible with most paint systems.
- ✓ **Full visual control:** The film is transparent. This allows quick and precise visual inspection and makes quality assurance very efficient.
- ✓ **Residue-free removal:** The adhesive system ensures clean and easy removal, in both warm and cold conditions and after an extended period of outdoor exposure – without the need for additional cleaning procedures.

[REQUEST A SAMPLE NOW!](#)

Please reach out to your dedicated POLIFILM Sales representative today and request your sample roll of 1698CLVHS.

